

Backlit Baner Ikonos Backlit 510

Product Technical Data Sheet:

General description:

White, matt coated PVC wich has very high resistance. Perfect for back-light applications.

Application:

Perfect for back-light applications.

Technical Data:

Weight: 510 g/m²

Structure: 1000x1000 (20x20)

Final roll specification:

Core : 3"

Core thickness (mm) : 4

Width (mm): 1,10-5,00 m

Length(m): 50

Item	Unit	Value	Test Method
Base Fabric	Denier	1000DX1000D	100% PES
Construction	Weaving/inch	20X20	/
Weight of fabric	Gsm/m ²	175+/-10	DIN53352 BS3424 Method5B
Weight of PVC	Gsm/m ²	335+/-10	DIN53352 BS3424 Method5B
Total weight	Gsm/m ²	510+/-20	DIN53352 BS3424 Method5B
Thickness	mm	0.42+/-0.02	DIN EN ISO 2286-3
Width	cm	Up to 500	/
Tensile Strength	N/5cm	Wrap 2200 Weft 1900	DIN53352 BS3424
Tearing Strength	N	Wrap 300 Weft 250	DIN53352 BS3424
Adhesion	N/5cm	80	DIN53352 BS3425 Method9B
Temperature Resistance	(°C)	-20~70	TDIN53352 BS3425 Method10